

MODEL TEVFF-10L VERTICAL FORM FILL SEAL, LARGE

GENERAL DESCRIPTION

The TUCS MOBILE FORM/FILL/SEAL LARGE FRAME PACKAGING MACHINE significantly reduces packaging labor and material costs. The Tucs vertical form-fill-seal is a simple, accurate, and easy to operate machine which forms a flexible lay-flat pouch that uses a film roll. The TEVFF-10L rolls the film into a tube and produces a seam with a final horizontal heat seal before separation with cutting blades. This versatile machine can make a variety of pouches and can readily accommodate wet products or a combination of wet and dry (two-part fills). Volumetric filling is accomplished by an onboard, highly accurate, repeatable, and gentle piston pump.



Large Frame Tucs Mobile Form/Fill/Seal Machine

CERTIFICATIONS

NSF/ANSI-169, ANSI/UL-763



TUCS Equipment, Inc.

755 County Road 18 S. • Princeton MN 55371 Phone 763-574-7475 Fax 763-574-7472 www.tucsequipment.com ITEM NO.

PROJECT

QUANTITY

AIA NO.

CONSTRUCTION & FEATURES

All stainless-steel construction type 316L product contact surfaces, type 304L elsewhere = Mounted on 4 locking swivel casters = No clutches or brakes to wear out = Quick changeover between pouch sizes = Lexan front and side guards = Up to 70 pouches per minute = Minimum pouch: 1 3/16" x 2" = Maximum pouch: 12" x 36"

POUCH FORMING

Automatic film tracking - Supplied with forming shoulder to yield a maximum 12["] lay-flat pouch (½–2 gallons)

HEAT SEALS

Single bar vertical lap seal approximately ¼["] wide Two horizontal heat seal bars one for top of pouch, other for bottom of following pouch

FILL NOZZLE

Fill nozzle extends into partially formed pouch to eliminate splashing \blacksquare Dripless cut-off prevents dripping between pouches \blacksquare Standard $2\frac{1}{2}$ nozzle sized for $1\frac{1}{4}$ particulate \blacksquare Other sizes available

VOLUMETRIC PISTON PUMP

Standard metering barrel quickly adjustable from 1 quart to 1 gallon per stroke **•** Rotary valve sized for hot fill (160°F–190°F fill temperatures) – other fill temperatures available **VERIFY TEMPERATURES •** Compressed air operation. No electrical connections required for pump **•** Spare Parts Kits for Bagger and Pump

CONTROLS

Allen Bradley Programmable Logic Controller (PLC), contained within NEMA 4X control box with remote diagnostics from the factory ■ Pendent-mounted menu driven touch screen (HMI) operator interface

EXIT CONVEYOR

Supports the pouch during filling and removes the pouch after separation • 40[°] long with 12[°] wide FDA approved belting • Variable speed drive

OPTIONS

- □ Fill temperature monitoring
- □ Thermal transfer printing on pouch (verify label size)
- Notched seal area for easy opening
- □ Integral pouch handle
- □ Cold fill pump accessories-verify temperature
- □ 1 pallet of film (12 rolls, 2500-ft long)
- □ Printer with 5 rolls of ribbon
- Spray curtain for film roll
- Pump Changeover Kit

Printed in the USA | Revised 10-07-20

TUCS COOK-CHILL & PACKAGING SOLUTIONS

MODEL TEVFF-10L

VERTICAL FORM FILL SEAL, LARGE

Scan this QR code with your smart phone to visit our website for more information.



INCLUDED AS STANDARD

- 2¹/₂" NOZZLE (FOR 1¹/₄" PARTICULATE)
- 10" SHOULDER
- HOT FILL PISTON FILLER ACCESSORIES (160°F 190°F)
- TEITP INLET TUBING PACKAGE
- 1/2" x 10' AIR HOSE
 - SPARE PARTS PACKAGE
- TEBK CLEANING BRUSH KIT


OPTIONS

ŧ.

(22.9)


48.0

- FILL TEMPERATURE MONITORING
- THERMAL TRANSFER PRINTING ON POUCH
- NOTCHED SEAL AREA FOR EASY OPENING
- INTEGRAL POUCH HANDLE
- COLD FILL PISTON FILLER ACCESSORIES
- 1 PALLET OF FILM (12 ROLLS, 2500' LONG)
- PRINTER W/5 ROLLS OF RIBBON
- SPRAY CURTAIN FOR FILM ROLL
- PISTON FILLER CHANGEOVER KIT (VERIFY PRIOR TO ORDERING)



55.1


- 76.5




7' CORD W/ NON-NEMA, WATER TIGHT, 20A, 120/208V, 3 PHASE, 4 POLE, 4 WIRE PLUG – (CONNECTING FEMALE RECEPTACLE INCLUDED)

UTILITIES		RECOMMENDED CLEARANCES	
DESCRIPTION	UTILITY CONNECTION	RIGHT SIDE	36"
ELECTRICAL	16 FLA @ 208 VAC/3 PH/60 HZ (22.5 FLA W/	BACK	36"
	INTEGRAL POUCH HANDLE OPTION)	LEFT SIDE	24"
AIR SUPPLY	1/2" QUICK DISCONNECT - 30 CFM @ 90 PSI		

½" X 10' AIR HOSE



3.0 DIA. FLEXIBLE INLET HOSE - TEITP



10/7/2020

SYM

 $^{()}$

A